

**Grafico di Intercambiabilità per l'aggiornamento di servovalvole tradizionali alle
Servovalvole Woodward HRT R-DDV®**

WOODWARD HRT	Portata LPM	ABEX	ATCHLEY	MOOG	ULTRA	PEGASUS	VICKERS	Interfaccia Cerchio Porte	Adattatore P/N
27A50F-4KXX (0.48" CP)	13.2	410 415	208A, 209 211A, 214 215A 218	771 772 760,73,62 773	4653 4655 4551	20, 122A 132A 142M 130, 131	SM4-10 SM4-12 SM4-20, SP4-25 SM4-15 KBDG4V-3	0.625" 0.780" 0.875" 0.937" Cetop 3	25001001-002 25001001-001 25001005 25001028-001 25001006
27C20F-3BXX (0.78" CP)	18.9	410 415	208A, 209 211A, 214 215A 218	771 772 760,73,62 773	4653 4655 4551 4657	20, 122A 132A 142M 130, 131	SM4-10 SM4-12 SM4-20, SP4-25 SM4-15	0.625" 0.780" 0.875" 0.937"	25001030-001 NESSUNO 25001019-001 25001029-001
27E50F-3BXX (0.875" CP)	37.8	415	211A, 214 215A 218	772 760,73,62 773	4655 4551 4657	132A 142M 140, 141	SM4-12 SM4-20, SP4-25 SM4-15	0.780" 0.875" 0.937"	25001031-001 NESSUNO 25001032-001
27E50F-4AXX (0.875" CP)	56.7		215A 218	760,73,62 773	4551 4657	162M 160, 161	SM4-20, SP4-25 SM4-15	0.875" 0.937"	NESSUNO 25001032-001
27G50F-3AXX (1.75" CP)	113.4		231, 242 240	62-300 78 641	4695 4652	180	SM4-30 SM4-40	DIAMOND 1.750" D05	25001027-001 NESSUNO 25001034-001
27G50F-5AXX (1.75" CP)	151.2		242 240 261	78 72 641	4695 4652 4550	180, 1160 1282	SM4-30 SM4-40	DIAMOND 1.750" 2.000" D05	25001027-001 NESSUNO 25001033-001 25001034-001
Opzioni elettriche di comando									
Segnali di Comando Standard					Segnali di Comando Opzionali				
+/- 5 Volts, +/- 10 Volts 4 - 20 mA, +/- 10 mA, +/- 20 mA, +/- 50 mA					0 - 10 Volts, +/- 2.5 Volts +/- 5 mA, +/- 8 mA, +/- 40 mA, +/- 100 mA				